

BENEFITS

INSTALLS WITH ADHESIVE - NO NOISE, NO ODOUR

Gerflor adhesives are solvent-free and therefore odourless. Find out more in the "Installation tips" section

WIDE CHOICE OF STYLES

More than 30 different styles:
 • Classic, rustic or modern wood look
 • Slate, concrete, metal

REALISTIC

Textured and matt finish surface
 4 bevelled edges

RESISTANT

0.3 mm or 0.55 mm wear layer
 Shock-resistant varnish

FOR HOUSEHOLD AND COMMERCIAL USE

European classification:
 • CLASSIC 30: 23/31
 • CLASSIC 55: 33/42

SUITABLE FOR HIGH-HUMIDITY ROOMS

Watertight and slip-resistant

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Clean with soapy water or neutral detergent



TECHNICAL CHARACTERISTICS

		CLASSIC 30				CLASSIC 55				
		Planks		Tiles		Planks		Tiles		
THICKNESS	mm	2				2.5				
WEAR LAYER THICKNESS	mm	0.30				0.55				
WEIGHT	g/m ²	3460				4410				
DIMENSIONS	cm	18,4 x 121,9	15,2 x 91,4	45,7 x 45,7	30,5 x 61	18,4 x 121,9	15,2 x 91,4	61 x 61	30,5 x 61	45,7 x 91,4
AREA PER BOX	m ²	3,36	3,33	3,34	3,35	3,37	3,33	3,35	3,35	3,34
TILES PER BOX	Tiles	15	24	16	18	15	24	9	18	8
SURFACE		Varnished				Varnished				
EUROPEAN CLASSIFICATION	Class	23 / 31				33 / 42				
FIRE RATING	Class	BflS1				BflS1				
SOUND INSULATION	dB	3				4				
WATER RESISTANCE		Compatible with wet rooms				Compatible with wet rooms				
RESIDENTIAL USE GARANTEE*	years	12				15				

* For more details on guarantee, see www.gerflor.com

INSTALLATION TIPS

- **TOOLS REQUIRED:** ruler, utility knife, tape measure
- Check that all planks have the same batch number
- Store the planks in the room, flat and face up, for 24 hours prior to installation

➤ PROFESSIONAL LAYING RECOMMENDED


PERM'ADHESIVE VINYL FLOOR ADHESIVE



- High bond strength
- Dry glue: for a clean, stain-free installation
- Allows repositioning for up to 6 hours after installation
- Designed to reduce trowel grooves
- Odourless: no solvents
- Excellent resistance to plasticizer migration
- Non-staining

COVERAGE APPROX: 25M² WITH 5L
CODE: 0607 0001

CLIM'ADHESIVE SPECIAL HIGH- / LOW-TEMPERATURE ADHESIVE



- Eliminates joint contraction / expansion
- Withstands extreme temperature variations (e.g. direct sun, drop in temperature)
- Sets in just 30 minutes
- Excellent grip
- Odourless: no solvents

COVERAGE APPROX: 20M² WITH 5L
CODE: 0608 0001

ENVIRONMENT



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- Soapy water cleaning